

# Drivetech 4x4 Winches

We've got you (re)covered



**Advanced dual speed winch technology**  
for maximum strength and fast line retrieval

Two models available - 9,500lb and 12,000lb

Multiple control box mounting options

IP67 waterproof rating

26m synthetic rope

Quiet operation

**Kit includes:**

2-in-1 wired and wireless remote control

High quality battery isolation switch

Remote mount control box socket

Aluminium hawse fairlead

**Drivetech**™ **4x4**  
...driven by quality



DRIVETECH4X4.COM.AU

	DT-D9500SR	DT-D12000SR
<b>Rated Line Pull</b>	9500 lb	12000 lb
<b>Rope Type</b>	Synthetic	Synthetic
<b>Rope Diameter x Length</b>	Ø 9.0mm x 26m	Ø 9.5mm x 26m
<b>Fairlead</b>	Aluminium Hawse	Aluminium Hawse
<b>Motor: 12VDC Series Wound</b>	5.5HP	6.0HP
<b>Gear Ratio (Low Speed)</b>	201.6:1	230.4:1
<b>Gear Ratio (High Speed)</b>	100.8:1	115.2:1
<b>Automatic Load Holding Brake</b>	✓	✓
<b>3-Stage Planetary Gear Train</b>	✓	✓
<b>Dual Speed Modes (High/Low Speed)</b>	✓	✓
<b>Overcurrent Protection (150A)</b>	✓	✓
<b>IP67 Waterproof Rating</b>	✓	✓
<b>2-in-1 Wireless Remote</b>	✓	✓
<b>Quiet Operation (&lt;95dB)</b>	✓	✓
<b>Winch Dimensions (mm)</b>	557 (L) x 244 (W) x 164 (H)	557 (L) x 244 (W) x 164 (H)
<b>Net Weight (kg)</b>	31.8	32.8

### 9500lb Dual Speed Winch (DT-D9500SR)

#### Performance at Low Speed - Gear Ratio: 201.6:1

Line Pull		Line Speed		Motor
lb	kg	ft/min	m/min	Amps
0	0	38.7	11.8	85
2375	1078	13.8	4.2	195
4750	2157	10.2	3.1	257
7125	3234	7.2	2.2	323
9500	4307	4.9	1.5	419

#### Performance at High Speed - Gear Ratio: 100.8:1

Line pull		Line Speed		Motor
lb	kg	ft/min	m/min	Amps
0	0	70.8	21.6	87

#### Above performance specs are based on first layer of drum

Layer	Rated Line Pull		Rope on Drum	
	lb	kg	ft	m
1	9500	4307	6.2	5
2	7700	3490	39	12
3	6500	2946	68.2	21
4	5700	2584	95	29

### 12000lb Dual Speed Winch (DT-D12000SR)

#### Performance at Low Speed - Gear Ratio: 230.4:1

Line Pull		Line Speed		Motor
lb	kg	ft/min	m/min	Amps
0	0	33.7	10.3	79
3000	1362	11.5	3.5	177
6000	2724	8	2.4	259
9000	4086	5.8	1.8	330
12000	5488	3.9	1.2	425

#### Performance at High Speed - Gear Ratio: 115.2:1

Line pull		Line Speed		Motor
lb	kg	ft/min	m/min	Amps
0	0	64.2	19.6	80

#### Above performance specs are based on first layer of drum

Layer	Rated Line Pull		Rope on Drum	
	lb	kg	ft	m
1	12000	5455	17.6	5.4
2	9530	4332	37	11.4
3	7920	3600	63	19.4
4	6770	3077	88	26.8

