

JULY 19  
RAP587A

## HI-RISE TOW BALL & RETENTION LOCKING PLATE KIT

The Mister Hitches Hi-Rise tow ball is designed to give the user a little extra coupling height to enable a level ride height of the trailer or caravan or for use with European style friction head trailer couplings (Retention Locking Plate is required when used on these friction couplings). The Hi-Rise tow ball sits approx. 24mm to 25mm higher than standard tow balls, the increased height ensures that the friction head couplings have adequate clearance from the trailer ball mount. To combat tow ball rotation, an anti-rotation retention mounting plate is included in the kit. The tow ball is mounted between grooves on the plate, preventing rotation of the tow ball when hooked up to a European style friction head trailer coupling. The 50 mm Hi-Rise tow ball is rated to 3500kg and meets the performance requirements of Australian Standard AS4177.2.

### FEATURES

- 50mm tow ball rated at 3500kg
- Tow ball is black oxide coated for corrosion protection
- Tow ball shank length is 65mm, diameter 22mm
- Zinc plated retention locking plate
- Retention plate suits 75mm wide ball mount platforms
- Retention plate and tow ball should be used together when used in conjunction with a European style friction head coupling. Eg. Al-ko aks coupling

All components of the kit are sold separately or as a complete kit.

**MH-TB50HRB** TOW BALL HI-RISE 50mm BLACK OXIDE  
**MH-TBRP** TOW BALL RETENTION LOCKING PLATE 75mm  
**MH-TBHRK** TOW BALL HI-RISE & RETENTION PLATE KIT



\*BALL MOUNT SOLD SEPARATELY

\*Pricing listed was correct at time of product bulletin preparation.  
 Manufacturers Names used for reference purposes only.