

FOR **PULL-OUT AWNINGS**

Use Ctrl + F, ₩ + F or Search Page on your Windows PC, Mac, iOS or Android device to find your awning make and model quickly.

NOTE: All HD Hitch variants are compatible with the HD Wall Mount, HD Lockable Wall Mount and HD Bracket ranges and are optional with every setup.

TAP or **CLICK** on the contents of the table (e.g. ✓) that correspond to your awning to be taken to the RacksBrax product page.

Track spacing (mm)	Brand	Model	Manufacturer's recommended # of brackets	8159 (2 load pts)	8179 (2 load pts)	8162 (2 load pts)	8180 (2 load pts)	8163 (3 load pts)	8181 (3 load pts)	8182 (3 load pts)	8183 (3 load pts)
Single	Rhino-Rack®	Sunseeker 2.5 Awning	2	✓ or		✓ or		✓ or		>	
	SUPA PEG®	Stand Easy ERV Rear Awning 1.3m	2		✓ or		✓ or		✓ or		>
33	SUPA PEG®	Stand Easy All Purpose	2		✓ or		✓ or		✓ or		~
33	SUPA PEG®	Stand Easy ERV Awning 2m	2		✓ or		✓ or		✓ or		~
	SUPA PEG®	Stand Easy ERV Awning 2.5m	2		✓ or		✓ or		✓ or		~
	23Zero®	23Zero Raven 2000 and 2500	2	✓ or		✓ or		✓ or		✓	
	Anaconda®	Dune series	2	✓ or		✓ or		✓ or		✓	
	ARB®	2.5m x 2.5m Awning	2	✓ or		✓ or		✓ or		✓	
50	ARB®	Aluminium Encased Awning 2.5m x 2.5m	2	✓ or		✓ or		✓ or		✓	
50	BCF®	XTM Car Awning 2m and 2.5m	2	✓ or		✓ or		✓ or		✓	
	BCF®	Wanderer	2	✓ or		✓ or		✓ or		~	
	CAOS®	Nomad Side Mounted Awning 2 x 3m, 2 x 2.5m, 2.5x2.5m	2	✓ or		✓ or		✓ or		✓	
	Darche®	Eclipse Slimline 2 x 2.5m	2	✓ or		✓ or		✓ or		✓	



Track spacing (mm)	Brand	Model	Manufacturer's recommended # of brackets	8159 (2 load pts)	8179 (2 load pts)	8162 (2 load pts)	8180 (2 load pts)	8163 (3 load pts)	8181 (3 load pts)	8182 (3 load pts)	8183 (3 load pts)
	Darche®	Eclipse Slimline 2.5 x 2.5m	2	✓ or		✓ or		✓ or		>	
	Drifta®	Stockton Awnings 2.5 x 2.5m	2	ТВС							
	Howling Moon®	Alu Awn	2	✓ or		✓ or		✓ or		~	
	Howling Moon®	Safari Awn	2	✓ or		✓ or		✓ or		>	
	Howling Moon®	Leisure Awn	2	✓ or		✓ or		✓ or		>	
	Ironman 4x4®	Instant 1.4m ,2m, 2.5m	2	✓ or		✓ or		✓ or		>	
	Powerful 4x4®	Kalahari Awning Tent 1.4 x 2.5m	2	✓ or		✓ or		✓ or		✓	
	Powerful 4x4®	Kalahari Awning Tent 2 x 2.5m	2	✓ or		✓ or		✓ or		>	
	Powerful 4x4®	Kalahari Awning Tent 2.5 x 2.5m	2	✓ or		✓ or		✓ or		>	
	тэм®	Awning 2.5 x 2.5m	2	✓ or		✓ or		✓ or		>	
	тэм®	Awning 2 x 2.5m	2	✓ or		✓ or		✓ or		>	
	Eezi-Awn®	S1000 2m, 2.5m	2	✓ or		✓ or		✓ or		>	
DRILL 2 x 45-50 centres	Eezi-Awn®	Retract 1.5m, 2m, 2.5m (and Black ver.)	2	✓ or		✓ or		✓ or		>	
	Eezi-Awn®	Retract 3m	2	✓ or		✓ or		✓ or		✓	



FOR WING-STYLE AWNINGS (180°) (FOR WING AWNINGS WITH MOUNT POINT SPACING GREATER THAN 100MM, USE RACKSBRAX XD HITCH)

Use Ctrl + F, 舞 + F or Search Page on your Windows PC, Mac, iOS or Android device to find your awning make and model quickly.

NOTE: All HD Hitch variants are compatible with the HD Wall Mount, HD Lockable Wall Mount and HD Bracket ranges and are optional with every setup.

TAP or CLICK on the contents of the table (e.g. ✓) that correspond to your awning to be taken to the RacksBrax product page.

Track spacing (mm)	Make	Model	Manufacturer's recommended # of brackets	8159 (2 load pts)	8179 (2 load pts)	8162 (2 load pts)	8180 (2 load pts)	8163 (3 load pts)	8181 (3 load pts)	8182 (3 load pts)	8183 (3 load pts)	8175 (2 load pts)	8176 (3 load pts)	8173 (2 load pts)	8174
33	SUPA PEG®	Outbound Supa Wing Valance 180° Awning	3	ТВС											
33	SUPA PEG®	Wing Awning 180° 2.1m Wide	2		✓ or		✓ or		✓ or		~				
100	Oztent®	Foxwing 180° Awning*+	2	✓ or		✓ or		✓ or		>		REQUIRED or	REQUIRED		
100+	FOR WING AWNINGS WITH MOUNT POINT SPACING GREATER THAN 100MM, USE RACKSBRAX XD HITCH.														

^{*} Also works with XD Hitch and no Adaptors but reduced headroom benefits are then lost but Foxwing brackets can be used.

⁺ Requires brackets with 50mm hole spacing - not Foxwing Brackets unless using XD Hitch (see XD Range Compatibility Chart).



FOR WING-STYLE AWNINGS (270°) (FOR WING AWNINGS WITH MOUNT POINT SPACING GREATER THAN 100MM, USE RACKSBRAX XD HITCH)

Use Ctrl + F, ₩ + F or Search Page on your Windows PC, Mac, iOS or Android device to find your awning make and model quickly.

NOTE: All HD Hitch variants are compatible with the HD Wall Mount, HD Lockable Wall Mount and HD Bracket ranges and are optional with every setup.

TAP or CLICK on the contents of the table (e.g. ✓) that correspond to your awning to be taken to the RacksBrax product page.

Track spacing (mm)	Make	Model	Manufacturer's recommended # of brackets	8159 (2 load pts)	8179 (2 load pts)	8162 (2 load pts)	8180 (2 load pts)	8163 (3 load pts)	8181 (3 load pts)	8182 (3 load pts)	8183 (3 load pts)	8175 (2 load pts)	8176 (3 load pts)	8173 (2 load pts)	8174
	Adventure Kings®	King Wing	3						✓ or		<u> </u>				
	Drifta®	Drifta Rapid Wing Awning	2		✓ or		✓ or		✓ or		✓				
33	SUPA PEG®	Camper Trailer Square Back Deluxe (2.1 to 3.5m)	2		✓ or		✓ or		✓ or		✓				
	SUPA PEG®	Rapid 4 Wing Deluxe Awning 2.4m	2		✓ or		✓ or		✓ or		✓				
	SUPA PEG®	Outbound Rapid 6 Wing Awning 2.4m Deluxe	3						✓ or		✓				
40**	Drifta®	Stockton 270 Freestanding	3					✓ or			~				
	CAOS®	Nomad 270° Base Awning	2	✓ or		✓ or		✓ or		✓ or	✓	REQUIRED or	REQUIRED		
80	CAOS®	Nomad 270° Bub Awning (for Jeep/Suzuki)	2	✓ or		✓ or		✓ or		✓ or	✓	REQUIRED or	REQUIRED		
80	Eezi-Awn®	Bat 270	2	✓ or		✓ or		✓ or		>		REQUIRED or	REQUIRED		
	Eezi-Awn®	Manta 270	2	✓ or		✓ or		✓ or		✓		REQUIRED or	REQUIRED		
93	CAOS®	Nomad 270+ Premium Awning	2					✓ or		~			REQUIRED		
	Oztent®	Foxwing 270° Awning*+	2	✓ or		✓ or		✓ or		✓		REQUIRED or	REQUIRED		
100	Rhino-Rack®	Batwing*	2	✓ or		✓ or		✓ or		✓		REQUIRED or	REQUIRED		
	Rhino-Rack®	Batwing (Compact)*	2	✓ or		✓ or		✓ or		~		REQUIRED or	REQUIRED		
101+			FOR WING A	WNINGS WI	TH MOUNT	POINT SPAC	ING GREATE	ER THAN 100	OMM, USE RA	ACKSBRAX X	KD HITCH.				

- * Also works with XD Hitch and no Adaptors but reduced headroom benefits are then lost but Foxwing brackets can be used.
- * Requires brackets with 50mm hole spacing not Foxwing Brackets unless using XD Hitch (see XD Range Compatibility Chart).
- ** Requires a single 8.5mm hole to be drilled in each of 3 supplied "T" brackets or standard Drifta RTT brackets as supplied.



FOR SHOWER TENT-, ENSUITE- OR CHANGE ROOM-STYLE AWNINGS

Use Ctrl + F, ₩ + F or Search Page on your Windows PC, Mac, iOS or Android device to find your awning make and model quickly.

NOTE: All HD Hitch variants are compatible with the HD Wall Mount, HD Lockable Wall Mount and HD Bracket ranges and are optional with every setup.

TAP or **CLICK** on the contents of the table (e.g. ✓) that correspond to your accessory to be taken to the RacksBrax product page.

Track spacing (mm)	Make	Model	Manufacturer's recommended # of brackets	8159 (2 load pts)	8179 (2 load pts)	8162 (2 load pts)	8180 (2 load pts)	8163 (3 load pts)	8181 (3 load pts)	8182 (3 load pts)	8183 (3 load pts)
45	Bundutec®	Bunducube Shower tent		✓ or		<u>~</u>					
	23Zero®	Shower tent		✓ or		~					
	Bushwakka (Australia)®	Shower tent		✓ or		~					
50	CAOS®	Nomad Shower Tent		✓ or		~					
50	Ironman 4x4®	Instant Ensuite Shower		✓ or		~					
	Kick Ass®	Shower Tent Awning		✓ or		~					
	Quick Pitch®	Quick-en-Suite Bag		✓ or		~					
DRILL 2 x 50 centres	Quick Pitch®	Quick-en-Suite Camp Shower (in Aluminium Box)		✓ or		✓					



FOR **RECOVERY BOARDS**

Use Ctrl + F, 器 + F or Search Page on your Windows PC, Mac, iOS or Android device to find your awning make and model quickly.

NOTE: All HD Hitch variants are compatible with the HD Wall Mount, HD Lockable Wall Mount and HD Bracket ranges and are optional with every setup.

TAP or CLICK on the contents of the table (e.g. ✓) that correspond to your accessory to be taken to the RacksBrax product page.

Track spacing (mm)	Make	Model	Manufacturer's recommended # of brackets	8159 (2 load pts)	8179 (2 load pts)	8162 (2 load pts)	8180 (2 load pts)	8163 (3 load pts)	8181 (3 load pts)	8182 (3 load pts)	8183 (3 load pts)	8175 (2 load pts)	8176 (3 load pts)	8173 (2 load pts)	8174
890	MAXTRAX®	Mk II*		V										REQUIRED and/or**	REQUIRED
890	MAXTRAX®	Xtreme*		V										REQUIRED and/or**	REQUIRED
	TRED®	1100*		✓										REQUIRED and/or**	REQUIRED
	TRED®	GT*		/										REQUIRED and/or**	REQUIRED ***
876-897	TRED®	HD*		✓										REQUIRED and/or**	REQUIRED
	TRED®	Pro*		✓										REQUIRED and/or**	REQUIRED ***
	TRED®	ARB x TRED Pro*		>										REQUIRED and/or**	REQUIRED ***

^{*} Using MAXTRAX® or TRED® Mounting pins (use with Accessory Bars or HD Accessory Plate or both-refer to website description and guides).

^{**} USED FOR RECOVERY BOARDS ON PLATFORMS RACKS WITH NORTH SOUTH SLATS OR FOR EXTRA HEIGHT ADJUSTMENT IN CONJUNCTION WITH HD ACCESSORY PLATE 8174.

^{***} USED FOR RECOVERY BOARDS ON ROOF RACK BARS OR PLATFORM RACKS WITH EAST WEST SLATS.



FOR **STORAGE TUBES AND BARRELS**

Use Ctrl + F, ₩ + F or Search Page on your Windows PC, Mac, iOS or Android device to find your awning make and model quickly.

NOTE: All HD Hitch variants are compatible with the HD Wall Mount, HD Lockable Wall Mount and HD Bracket ranges and are optional with every setup.

TAP or CLICK on the contents of the table (e.g. ✓) that correspond to your accessory to be taken to the RacksBrax product page.

Diameter (mm)	Make	Model	Manufacturer's recommended # of brackets	8159 (2 load pts)	8179 (2 load pts)	8162 (2 load pts)	8180 (2 load pts)	8163 (3 load pts)	8181 (3 load pts)	8182 (3 load pts)	8183 (3 load pts)	8175 (2 load pts)	8176 (3 load pts)	8173 (2 load pts)	8174
100	Rhino-Rack®	Tube Clamp for 100mm diameter tube		✓ or		✓ or		✓ or		✓					
150	Rhino-Rack®	Tube Clamp for 150mm diameter tube		✓ or		✓ or		✓ or		✓					