

XD HITCH RECOMMENDED CONFIGURATIONS

HOW MANY HITCHES SHOULD I USE FOR MY AWNING?

The XD Hitch is sold in Double or Triple packs. Download the PDF Compatibility Chart for a summary of the minimum number of XD Hitches needed for various awning types with mounting spacings from 100mm to 120mm; including triple spine awning tracks with 2 x 60mm centres such as the Howling Moon range.

The table below outlines the minimum number of XD Hitches needed for various awning types:

1. Firstly, the number of XD Hitches **must not be less** than the number of brackets (support points) recommended by the awning manufacturer.
2. Secondly, for a given wing awning type, the table below outlines the minimum number of XD Hitches needed, which **may** exceed quantities in 1 above. Ensure you satisfy the requirement of each column for your given awning whilst ensuring you also comply with 1 above.

WING TYPE	ROOF AREA m ² (ft ²)	MAXIMUM awning weight kg (lbs)*	MINIMUM # of XD Hitches (and thus brackets)
180° and 270°	≤11.5m ² (124 ft ²)	40kg (88lb)	2 (1 x 9000)
180° and 270°	>11.5m ² (124 ft ²)	60kg (132lb)	3 (1 x 9001)
360°	>11.5m ² (124 ft ²)	80kg (176lb)	4 (2 x Double 9000)

* **Loads must not exceed the rated load capacity of the XD Hitch, the bracket, the roof rack or the vehicle manufacturers specifications.**